(in accordance with Regulation (EU) 2015/830)

FPM 201 lustre iris

Version: 7 Page 1 of 17
Revision date: 30/08/2018 Print date: 30/08/2018

SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: FPM 201 lustre iris

1.2 Relevant identified uses of the mixture and uses advised against.

Ceramic use.

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: GLAZURA, S.R.O.

Address: Roudnická 122 City: 413 01 Dobrín Telephone: +420 416 809 711

Fax: +420 416 809 814, +420 416 809 733

E-mail: info@glazura.cz

1.4 Emergency telephone number: (Available 24 hours)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the mixture.

In accordance with Regulation (EU) No 1272/2008:

Aquatic Chronic 2: Toxic to aquatic life with long lasting effects.

Eye Dam. 1: Causes serious eye damage. Flam. Liq. 3: Flammable liquid and vapour. Skin Irrit. 2: Causes skin irritation.

Skin Sens. 1 : May cause an allergic skin reaction. STOT SE 3 : May cause respiratory irritation. STOT SE 3 : May cause drowsiness or dizziness.

2.2 Label elements.

<u>Labelling in accordance with Regulation (EU) No 1272/2008: Pictograms:</u>









Signal Word: Danger

H statements:

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
	and the second s

H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

P statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

(in accordance with Regulation (EU) 2015/830)

Z2250122L Lustre

 Version: 7
 Page 2 of 17

 Revision date: 30/08/2018
 Print date: 30/08/2018

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor/...
P321 Specific treatment (see ... on this label).
P370+P378 In case of fire: Use... to extinguish.

EUH statements:

EUH208 Contains Dipentene. May produce an allergic reaction.
EUH208 Contains delta-3-Carene. May produce an allergic reaction.
EUH208 Contains Rosemary oil N. Afr.. May produce an allergic reaction.

Contains: cyclohexanol Rosin titanium tetrabutanolate Eucalyptus globulus oil Pine exctract

2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

			(*)Classification - Regulation (EC) No 1272/2008		
Identifiers	Identifiers Name Conce		Classification	specific concentration limit	
Index No: 603-009- 00-3 CAS No: 108-93-0 EC No: 203-630-6 Registration No: 012119447488-26- XXXX	[1] cyclohexanol	>=10% <25%	Acute Tox. 4 *, H332 - Acute Tox. 4 *, H302 - Skin Irrit. 2, H315 - STOT SE 3, H335	-	
CAS No: 84625-32-1 EC No: 283-406-2	Eucalyptus globulus oil	>=10% <25%	Aquatic Chronic 2, H411 - Asp. Tox. 1, H304 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	-	
CAS No: 5593-70-4 EC No: 227-006-8	titanium tetrabutanolate	>=10% <25%	Eye Dam. 1, H318 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315 - STOT SE 3, H335 - STOT SE 3, H336	-	

(in accordance with Regulation (EU) 2015/830)

FPM 201 lustre iris

 Version: 7
 Page 3 of 17

 Revision date: 30/08/2018
 Print date: 30/08/2018




CAS No: 94266-48-5 EC No: 304-455-9	Pine exctract	>=5% <10%	Aquatic Acute 1, H400 - Aquatic Chronic 1, H410 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315 - Skin Sens. 1, H317 - Skin Sens. 1A, H317	-
CAS No: 8000-41-7 EC No: 232-268-1 Registration No: 012119553062-49- XXXX	Terpineol	>=2.5% <5%	Eye Irrit. 2, H319 - Skin Irrit. 2, H315	-
CAS No: 8052-42-4 EC No: 232-490-9 Registration No: 012119480172-44- XXXX	[1] Asphalt	>=2.5% <5%	-	-
Index No: 601-025- 00-5 CAS No: 108-67-8 EC No: 203-604-4 Registration No: 012119463878-19- XXXX	[1] 1,3,5-trimethylbenzene,mesitylene	>=2.5% <5%	Aquatic Chronic 2, H411 - Flam. Liq. 3, H226 - STOT SE 3, H335	STOT SE 3, H335: C ≥ 25 %
CAS No: 68956-56-9 EC No: 273-309-3	Hydrocarbons, terpene processing by-products	>=1% <2.5%	Asp. Tox. 1, H304 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315	-
Index No: 650-015- 00-7 CAS No: 8050-09-7 EC No: 232-475-7 Registration No: 012119480418-32- XXXX	[1] Rosin	>=1% <2.5%	Skin Sens. 1, H317	-
CAS No: 99-86-5 EC No: 202-795-1	alpha-Terpinene	>=1% <2.5%	Acute Tox. 4, H302 - Aquatic Chronic 2, H411 - Asp. Tox. 1, H304 - Flam. Liq. 3, H226	-
CAS No: 8000-25-7 EC No: 283-291-9	Rosemary oil N. Afr.	>=0.1% <1%	Acute Tox. 4, H332 - Aquatic Acute 1, H400 - Aquatic Chronic 1, H410 - Asp. Tox. 1, H304 - Flam. Liq. 3, H226 - Skin Sens. 1, H317 - STOT SE 2, H371	-

(in accordance with Regulation (EU) 2015/830)

Z2250122L Lustre

Version: 7 Page 4 of 17
Revision date: 30/08/2018 Print date: 30/08/2018



^(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

SECTION 4: FIRST AID MEASURES.

IRRITANT PREPARATION. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eye contact.

Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Dont let the person to rub the affected eye.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.


^{*} See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

^[1] Substance with a Community workplace exposure limit (see section 8.1).

(in accordance with Regulation (EU) 2015/830)

FPM 201 lustre iris

Version: 7 Page 5 of 17
Revision date: 30/08/2018 Print date: 30/08/2018



Contact with eyes may cause irreversible damage.

It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

4.3 Indication of any immediate medical attention and special treatment needed.

Request immediate medical attention. Never administer anything orally to persons who are unconscious. Do not induce vomiting. If the person vomits, clear the respiratory tract. Cover the affected area with a dry sterile bandage. Protect the affected area from pressure or friction.

SECTION 5: FIREFIGHTING MEASURES.

Flammable product, the necessary prevention measures should be taken in order to avoid risks, In case of fire, the following measures are recommended:

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the mixture.

Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:

- Flammable vapors or gases.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment. Follow the instructions given in the emergency or fire evacuation plan or plans if available.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Pick up the spill with non-combustible absorbent materials (soil, sand, vermiculite, diatomite, etc.). Pour the product and the absorbent in an appropriate container. The contaminated area should be immediately cleaned with an appropriate decontaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

(in accordance with Regulation (EU) 2015/830)

Z2250122L Lustre

Version: 7 Page 6 of 17
Revision date: 30/08/2018 Print date: 30/08/2018



For exposure control and individual protection measures, see section 8. For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use antistatic footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks.For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 35° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

Classification and threshold amount of storage in accordance with Annex I to Directive 2012/18/EU (SEVESO III):

		Qualifying quant the applic	* ` `
Code	Description	Lower-tier requirements	Upper-tier requirements
E2	ENVIRONMENTAL HAZARDS - Hazardous to the Aquatic Environment in Category Chronic 2	200	500

7.3 Specific end use(s).

Not available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m³
	Koninkrijk België/Royaum e de Belgique/König reich Belgien [1] 108-93-0 United Kingdom [2] United States [3] (Cal/OSHA) United States [4] (NIOSH)	België/Royaum e de Belgique/König reich Belgien	Eight hours	50	209
			Short term		
cyclohexanol			Eight hours	50	208
			Short term		
			Eight hours	50	
			Short term		
		United States	Eight hours	50	
		Short term			

(in accordance with Regulation (EU) 2015/830)

FPM 201 lustre iris

 Version: 7
 Page 7 of 17

 Revision date: 30/08/2018
 Print date: 30/08/2018

		United States 5 (OSHA)	Eight hours Short term	50	200
Asphalt	8052-42-4	Koninkri k elgi /Royaum e de elgique/K nig reich elgien 1	Eight hours Short term		5
		United Kingdom 2	Eight hours Short term		5 10
1,3,5-trimethylbenzene,mesitylene	108-67-8	Koninkri k elgi /Royaum e de elgique/K nig reich elgien 1	Eight hours Short term	20	100
		European Union 6	Eight hours Short term	20	100
Rosin	8050-09-7	United Kingdom 2	Eight hours Short term		0,05 0,15
Camphor	76-22-2	Koninkri k	Eight hours	2	12
		elgi /Royaum e de elgique/K nig reich elgien 1	Short term	3	19
delta-3-Carene	13466-78-9	Koninkri k elgi /Royaum e de elgique/K nig reich elgien 1	Eight hours Short term	20	
3,7,7-trimethylbicyclo 4.1.0 hept-3-ene	13466-78-9	Koninkri k elgi /Royaum e de elgique/K nig reich elgien 1	Eight hours Short term	20	

- 1 According " aleurs Limites d Exposition Professionnelle" (LEP) or " renswaarden voor eroepsmatige lootstelling" (W) list adopted by elgian Ministry of Employment and Labour.
- 2 According Limit alue (IOEL) list in 2nd Indicative Occupational Exposure adobted by Health and Safety Executive.
- 3 California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).
- 4 National Institute for Occupational Safety and Health. NIOSH Recommendations for occupational safety and health, Compendium of Policy Documents and Statements, anuary, 1992, DHHS (NIOSH) Publication No. 92-100.
- 5 Occupational Safety and Health Administration, United States Department of Labor. Permissible Exposure limits (PELs), California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).
- 6 According both inding Occupational Esposure Limits (OEL s) and Indicative Occupational Exposure Limits (IOEL s) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

The product does NOT contain substances with iological Limit alues. Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Туре	Value
cyclohexanol CAS No: 108-93-0 EC No: 203-630-6	DNEL (Workers)	Inhalation, Long-term, Systemic effects	130 (mg/m3)

GLAZURA

(in accordance with Regulation (EU) 2015/830)

Z22 0122L Lustre

 Version: 7
 Page 8 of 17

 Revision date: 30/08/2018
 Print date: 30/08/2018



Terpineol CAS No: 8000-41-7 EC No: 232-268-1	DNEL (Workers)	Inhalation, Long-term, Systemic effects	5,8 (mg/m)
Asphalt CAS No: 8052-42-4 EC No: 232-490-9	DNEL (Workers)	Inhalation, Long-term, Local effects	2,9 (mg/m)
1,3,5-trimethylben ene,mesitylene CAS No: 108-67-8 EC	DNEL (Workers)	Inhalation, Long-term, Local effects	100 (mg/m)
No: 203-604-4	DNEL (Workers)	Inhalation, Long-term, Systemic effects	100 (mg/m)
Rosin CAS No: 8050-09-7 EC No: 232-475-7	DNEL (Workers)	Inhalation, Long-term, Systemic effects	176 (mg/m)
delta-3-Carene CAS No: 13466-78-9 EC No: 236-719-3	DNEL (Workers)	Inhalation, Long-term, Systemic effects	5,98 (mg/m)
3,7,7-trimethylbicyclo[4.1.0]hept-3-ene CAS No: 13466-78-9 EC No: 236-719-3	DNEL (Workers)	Inhalation, Long-term, Systemic effects	5,98 (mg/m)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Ceramic use.
on:
Filter mask for protection against gases and particles (A-P).
Category I, II or III should be chosen depending on the use limit value. The mask
be comfortable and tight to the face.
EN 149
Avoid exposure to high temperatures when not used. Before use, check the integrity of and
ce: expiration valves.
Use when exceeding TL for one or more substances conteined in the mixture. Be sure that uipment is efficient.
uipment is emdent.
Protective gloves against chemicals.
CE marking, category III.
-
_
EN 374-1, En 374-2, EN 374-3, EN 420
away from any sources of heat, and avoid exposure to sunlight as much Maintenance: Do s p _{ossible} . not make any changes to the gloves that may alter their resistance, or apply paints, solvints in
adhesives. loves should be of the appropriate si e and fit the users hand well, not being too loose or $t_{o_i}^{\mathfrak{I}}$ ght.
Always use with clean, dry hands.

(in accordance with Regulation (EU) 2015/830)

FPM 201 lustre iris

 Version: 7
 Page of 17

 Revision date: 30/08/2018
 Print date: 30/08/2018

Breakthrough time Material thickness 0, Material: P C (polyvinyl chloride > 480 (mm): (min<u>.):</u> E e protection: Protective goggles against splashes and particles. Characteristics: CEN standards: Maintenance: Under normal and reasonably foreseeable conditions, eye protection is not required. However, protective Observations: goggles are recommended when handling the product to avoid accidental sketching of liquids. S in protection: If the product is handled correctly, no individual protection equipment is necessary.

SECTION: PHYSICAL AND CHEMICAL PROPERTIES.

.1 Information on basic ph sical and chemical properties.

Appearance: Liquid with characteristic odour and colour

Colour: not available Odour:characteristic Odour threshold:not available

pH:N.A./N.A.

Melting point:not available C

Boiling Point: 174 C Flash point: 53 C

Evaporation rate: not available

Inflammability (solid, gas): not available

Lower Explosive Limit: It does not contain chemical groups associated with explosive properties Upper Explosive Limit: It does not contain chemical groups associated with explosive properties

apour pressure: 0,756 apour density:not available Relative density:0,959 Solubility: N.A./N.A. Liposolubility: N.A./N.A. Hydrosolubility: N.A./N.A.

Partition coefficient (n-octanol/water): not available Auto-ignition temperature: not available C Decomposition temperature: not available C

iscosity: N.A./N.A.

Explosive properties: It does not contain chemical groups associated with explosive properties Oxidi ing

properties: It does not contain chemical groups associated with oxdi ing properties

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

.2 Other information.

Pour point: not available Blink: not available

inematic viscosity: N.A./N.A.

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

SECTION 10: STA ILITY AND REACTIVITY.

10.1 Reactivit .

If the storage conditions are satisfied, does not produce dangerous reactions.

10.2 Chemical stabilit .

(in accordance with Regulation (EU) 2015/830)

Z2250122L Lustre

Version: 7 Revision date: 30/08/2018



Page 10 of 17 Print date: 30/08/2018

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibilit of hazardous reactions.

Flammable liquid and vapour.

10. Conditions to avoid.

Avoid the following conditions:

- High temperature.
- Static discharge.
- Contact with incompatible materials.
- Avoid temperatures near or above the flash point. Do not heat closed containers. Avoid direct sunlight and heat, as these may cause a risk of fire.

10.5 Incompatible materials. Avoid

the following materials:

- Explosives materials.
- Toxic materials.
- Oxidi ing materials.

10. Hazardous decomposition products.

In case of fire, dangerous decomposition products can be generated, such as carbon monoxide and dioxide and nitrogen fumes and oxides.

SECTION 11: TO ICOLOGICAL INFORMATION.

IRRITANT PREPARATION. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

IRRITANT PREPARATION. The inhalation of spray mist or suspended particulates can irritate the respiratory tract. It can also cause serious respiratory difficulties, central nervous system disorders, and in extreme cases, unconsciousness.

11.1 Information on toxicological effects.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Toxicological information about the substances present in the composition.

Name		Acute tαicit			
	T pe	Test	ind	Value	
		Oral	LD50	RAT	1400 mg/kg
cyclohexanol		Dermal	LD50	Rabbit	5000 mg/ g
		Inhalation	CL50	Rat	3.6 mg/L [1]
CAS No: 108-93-0	EC No: 203-630-6	maladon	[1] OECD	Test uideline 103	3
		Oral			
1,3,5-trimethylben en	e,mesitylene	Dermal			
		Inhalation	LC50	Rat	24 mg/l/4 h [1]
CAS No: 108-67-8	EC No: 203-604-4			na i Sanitariya. For), Pg. 15, 1979	English translation, see HYSAA .
Rosin		Oral	DL50	Rat	2800 mg/ g
CAS No: 8050-09-7	EC No: 232-475-7	Dermal			

(in accordance with Regulation (EU) 2015/830)

FPM 201 lustre iris

 Version: 7
 Page 11 of 17

 Revision date: 30/08/2018
 Print date: 30/08/2018



	Inhalation			
	Oral	LD50	Торо	1400 mg/kg
Camphor	Dermal	LD50	Ratto	2000 mg/kg
CAS No: 76-22-2 EC No: 200-945-0	Inhalation	LC50	Ratto	500 mg/kg
	Oral	LD50 LD50	Rat Rat	4800 mg/kg [1] 4800 mg/kg [2]
3,7,7-trimethylbicyclo[4. l.0]hept-3-ene	Oral	[1] [2]	1 Cosmetics Toxicology 1 Cosmetics Toxicology	
	Dermal			
CAS No: 13466-78-9 EC No: 236-719-3	Inhalation			

a) acute toxicity

Not conclusive data for classification.

Acute Toxicity Estimate (ATE):

Mixtures:

ATE (Oral) = 2.297 mg/kg

b) skin corrosion/irritation Product classified:

Skin irritant, Category 2: Causes skin irritation.

c) serious eye damage/irritation Product classified:

Serious eye damage, Category 1: Causes serious eye damage.

d) respiratory or skin sensitisation Product classified:

Skin sensitiser, Category 1: May cause an allergic skin reaction.

- e) germ cell mutagenicity Not conclusive data for classification.
- f) carcinogenicity

Not conclusive data for classification.

- g) reproductive toxicity Not conclusive data for classification.
- h) STOT-single exposure Product classified:

Specific target organ toxicity following a single exposure, Category 3:

i) STOT-repeated exposure

Not conclusive data for classification.

) aspiration ha ard

Based on available data, the classification criteria are not met.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicit .

(in accordance with Regulation (EU) 2015/830)

Z2250122L Lustre

Version: 7 Revision date: 30/08/2018



Page 12 of 17 Print date: 30/08/2018

	Ecotoxicit				
Name	T pe	Test	ind	Value	
	Fish	LC50 Fish 12,5 r [1] Brenniman, ., R. Hartung, and W W Continuous Flow Bioassay Method to Evalu Outboard Motor Exhausts and Selected Arc on Fish. Water Res. 10(2):165-169			
	Aquatic invertebrates	LC50 Crustacean 13 mg/l (48 h) [1 [1] Caldwell, R.S., E.M. Caldarone, and M.H. Mallon 19 Effects of a Seawater-Soluble Fraction of Cook Inlet Cr			
1,3,5-trimethylben ene,mesitylene CAS No: 108-67-8 EC No: 203-604-4	Aquatic plants				

12.2 Persistence and degradabilit .

There is no information available on the degradability of the substances present.

No information is available regarding the degradability of the substances present. No information is available about persistence and degradability of the product.

12.3 ioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name	ioaccumulation			
name	Log Po	CF	NOECs	Level
1,3,5-trimethylben ene,mesitylene N. CAS: 108-67-8 EC No: 203-604-4	3,42	-	-	Moderate
delta-3-Carene N. CAS: 13466-78-9 EC No: 236-719-3	4,38	-	-	High
3,7,7-trimethylbicyclo[4.1.0]hept-3-ene N. CAS: 13466-78-9 EC No: 236-719-3	4,38	-	-	High

12. Mobilit in soil.

No information is available about the mobility in soil. The product must not be allowed to go into sewers or waterways. Prevent penetration into the ground.

12.5 Results of P T and vPv assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12. Other adverse effects.

No information is available about other adverse effects for the environment.

(in accordance with Regulation (EU) 2015/830)

FPM 201 lustre iris

 Version: 7
 Page 13 of 17

 Revision date: 30/08/2018
 Print date: 30/08/2018



13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions **Sea**: Transport by ship: IMDG. Transport documentation: Bill of

lading Air: Transport by plane: ICAO/IATA.

Transport document: Airway bill.

14.1 UN number. UN No: UN1263

011 1101 0111203

14.2 UN proper shipping name.

Description:

ADR: UN 1263, PAINT RELATED MATERIAL, 3, PG III, (D/E)

IMDG: UN 1263, PAINT RELATED MATERIAL (EUCALYPTUS GLOBULUS OIL), 3, PG III, MARINE POLLUTANT

ICAO/IATA: UN 1263, PAINT RELATED MATERIAL, 3, PG III

14.3 Transport hazard class(es).

Class(es): 3

14.4 Packing group.

Packing group: III

14.5 Environmental hazards.

Marine pollutant: Yes



Dangerous for the environment

14.6 Special precautions for user.

Labels: 3



Hazard number: 30 ADR LQ: 5 L IMDG LQ: 5 L

ICAO LQ: 10 L

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR. Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-E,S-E Proceed in accordance with point 6.

(in accordance with Regulation (EU) 2015/830)

Z2250122L Lustre

Version: 7 Revision date: 30/08/2018



Page 14 of 17 Print date: 30/08/2018

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code. The product is not transported in bulk.

(in accordance with Regulation (EU) 2015/830)

Z2250122L Lustre

Version: 7 Page 15 of 17
Revision date: 30/08/2018 Print date: 30/08/2018



SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC) VOC content (p/p): 26,488 % VOC content: 254,141 g/l

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): E2

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

11221	Extremely numbre inquia and vapour.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H371	May cause damage to organs.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Extremely flammable liquid and vapour.

Classification codes:

H224

Acute Tox. 4 : Acute toxicity (Inhalation), Category 4 Acute Tox. 4 : Acute toxicity (Oral), Category 4

Aquatic Acute 1: Acute toxicity to the aquatic environment, Category 1

Aquatic Chronic 1: Chronic effect to the aquatic environment, Category 1 Aquatic

Chronic 2 : Chronic effect to the aquatic environment, Category 2

Asp. Tox. 1 : Aspiration toxicity, Category 1 Eye Dam. 1 : Serious eye damage, Category 1 Eye

Irrit. 2: Eye irritation, Category 2

Flam. Liq. 1: Flammable liquid, Category 1 Flam. Liq. 3: Flammable liquid, Category 3 Flam. Sol. 2: Flammable solid, Category 2 Skin Irrit. 2: Skin irritant, Category 2 Skin Sens. 1: Skin sensitiser, Category 1 Skin Sens. 1A: Skin sensitiser, Category 1A

(in accordance with Regulation (EU) 2015/830)

Z2250122L Lustre



GLAZURA

STOT SE 2 : Specific target organ toxicity following a single exposure, Category 2 STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3 **Revision**

date: 30/08/2018 Print date: 30/08/2018

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Information on the TSCA Inventory (Toxic Substances Control Act) USA:

CAS No	Name	State
108-93-0	cyclohexanol	Registered
84625-32-1	Eucalyptus globulus oil	
5593-70-4	titanium tetrabutanolate	Registered
94266-48-5	Pine exctract	
8000-41-7	Terpineol	Registered
8052-42-4	Asphalt	Registered
108-67-8	1,3,5-trimethylbenzene,mesitylene	Registered
68956-56-9	Hydrocarbons, terpene processing by-products	Registered
8050-09-7	Rosin	Registered
99-86-5	alpha-Terpinene	Registered
8000-25-7	Rosemary oil N. Afr.	Registered
76-22-2	Camphor	Registered
138-86-3	Dipentene	Registered
13466-78-9	delta-3-Carene	Registered
13466-78-9	3,7,7-trimethylbicyclo[4.1.0]hept-3-ene	Registered

Abbreviations and acronyms used:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

BCF: Bioconcentration factor.

CEN: European Committee for Standardization.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be

considered a tolerable minimum.

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not

anticipated.

EC50: Half maximal effective concentration.

PPE: Personal protection equipment.

IATA: International Air Transport Association.

ICAO: International Civil Aviation Organization.

IMDG: International Maritime Code for Dangerous Goods.

LC50: Lethal concentration, 50%.

LD50: Lethal dose, 50%.

Log Pow: Logarithm of the partition octanol-water. NOEC: No observed effect concentration.

RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

Key literature references and sources for data:

http://eur-lex.europa.eu/homepage.html

http://echa.europa.eu/ Regulation

(EU) 2015/830.

Regulation (EC) No 1907/2006. Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive

-

(in accordance with Regulation (EU) 2015/830)

Z2250122L Lustre



Version: 7 Page 17 of 17

1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.

End of safety data sheet.-