(in accordance with Regulation (EU) 2015/830)

# FPM 302 Platinum light

 Version: 6
 Page 1 of 19

 Revision date: 30/08/2018
 Print date: 30/08/2018

## SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

#### 1.1 Product identifier.

Product Name: FPM 302 Platinum light

1.2 Relevant identified uses of the mixture and uses advised against.

Ceramic use.

### Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: GLAZURA, S.R.O.

Address: Roudnická 122 City: 413 01 Dobrín Telephone: +420 416 809 711

Fax: +420 416 809 814, +420 416 809 733

E-mail: info@glazura.cz

1.4 Emergency telephone number: (Available 24 hours)

### **SECTION 2: HAZARDS IDENTIFICATION.**

### 2.1 Classification of the mixture.

In accordance with Regulation (EU) No 1272/2008:

Aquatic Chronic 2: Toxic to aquatic life with long lasting effects.

Flam. Liq. 3: Flammable liquid and vapour.

Skin Irrit. 2 : Causes skin irritation.

Skin Sens. 1: May cause an allergic skin reaction.

### 2.2 Label elements.

## <u>Labelling in accordance with Regulation (EU) No 1272/2008: Pictograms:</u>







# Signal Word:

# Warning

H statements:

H226 Flammable liquid and vapour. H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.

P statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P321 Specific treatment (see ... on this label).
P370+P378 In case of fire: Use... to extinguish.
P403+P235 Store in a well-ventilated place. Keep cool.

(in accordance with Regulation (EU) 2015/830)

# Z2380018L Platinum

 Version: 6
 Page 2 of 19

 Revision date: 30/08/2018
 Print date: 30/08/2018

P501 Dispose of contents/container to ...

**EUH statements:** 

EUH208 Contains Dipentene. May produce an allergic reaction.
EUH208 Contains delta-3-Carene. May produce an allergic reaction.

EUH208 Contains 2-Naphthalenol, 1-[[4-(phenylazo)phenyl]azo]-, ar',ar''-Me derivs.. May produce an allergic reaction.

Contains: Rosin

Rosemary oil N. Afr. Eucalyptus globulus oil

Pine exctract

### 2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

### 3.1 Substances.

Not Applicable.

### 3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

			(*)Classification - Regulation (		
Identifiers	Name	Concentrate			
CAS No: 84625-32-1 EC No: 283-406-2	Eucalyptus globulus oil	>=25% <50%	Aquatic Chronic 2, H411 - Asp. Tox. 1, H304 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	-	
CAS No: 8000-25-7 EC No: 283-291-9	Rosemary oil N. Afr.	>=5% <10%	Acute Tox. 4, H332 - Aquatic Acute 1, H400 - Aquatic Chronic 1, H410 - Asp. Tox. 1, H304 - Flam. Liq. 3, H226 - Skin Sens. 1, H317 - STOT SE 2, H371	-	
Index No: 606-010- 00-7 CAS No: 108-94-1 EC No: 203-631-1 Registration No: 012119453616-35- XXXX	[1] cyclohexanone	>=2.5% <5%	Acute Tox. 4 *, H332 - Flam. Liq. 3, H226	-	

(in accordance with Regulation (EU) 2015/830)

# **FPM 302 Platinum light**





CAS No: 76-22-2 EC No: 200-945-0 Registration No: 012119966156-31- XXXX	[1] Camphor	>=2.5% <5%	Acute Tox. 4, H302 - Eye Irrit. 2, H319 - Flam. Sol. 2, H228 - Skin Irrit. 2, H315 - STOT SE 3, H335	-
Index No: 650-015- 00-7 CAS No: 8050-09-7 EC No: 232-475-7 Registration No: 012119480418-32- XXXX	[1] Rosin	>=2.5% <5%	Skin Sens. 1, H317	-
CAS No: 94266-48-5 EC No: 304-455-9	Pine exctract	>=2.5% <5%	Aquatic Acute 1, H400 - Aquatic Chronic 1, H410 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315 - Skin Sens. 1, H317 - Skin Sens. 1A, H317	-
Index No: 601-025- 00-5 CAS No: 108-67-8 EC No: 203-604-4 Registration No: 012119463878-19- XXXX	[1] 1,3,5-trimethylbenzene,mesitylene	>=2.5% <5%	Aquatic Chronic 2, H411 - Flam. Liq. 3, H226 - STOT SE 3, H335	STOT SE 3, H335: C ≥ 25 %
CAS No: 68956-56-9 EC No: 273-309-3	Hydrocarbons, terpene processing by-products	>=1% <2.5%	Asp. Tox. 1, H304 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315	-
CAS No: 99-86-5 EC No: 202-795-1	alpha-Terpinene	>=1% <2.5%	Acute Tox. 4, H302 - Aquatic Chronic 2, H411 - Asp. Tox. 1, H304 - Flam. Liq. 3, H226	-
Index No: 601029007 CAS No: 138-86-3 EC No: 205-341-0	Dipentene	>=0.1% <1%	Aquatic Acute 1, H400 (M=1) - Aquatic Chronic 1, H410 (M=1) - Flam. Liq. 1, H224 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	-
CAS No: 13466-78-9 EC No: 236-719-3 Registration No: 012119520252-55- XXXX	[1] delta-3-Carene	>=0.1% <1%	Asp. Tox. 1, H304 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	-

(in accordance with Regulation (EU) 2015/830)

# Z2380018L Platinum

Version: 6 Page 4 of 19
Revision date: 30/08/2018 Print date: 30/08/2018

CAS No: 70879-65-1 EC No: 274-972-1	2-Naphthalenol, 1-[[4-(phenylazo)phenyl]azo]-, ar',ar"-Me derivs.	>=0.1% <1%	Carc. 2, H351 - Muta. 2, H341 - Skin Sens. 1B, H317	-
CAS No: 13466-78-9 EC No: 236-719-3 Registration No: 012119520252-55- XXXX	[1] 3,7,7-trimethylbicyclo[4.1.0]hept-3-ene	>=0.1% <1%	Aquatic Chronic 2, H411 - Asp. Tox. 1, H304 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315	-
CAS No: 8052-42-4 EC No: 232-490-9 Registration No: 012119480172-44- XXXX	[1] Asphalt	>=0.1% <1%	-	-

(\*)The complete text of the H phrases is given in section 16 of this Safety Data

Sheet. \* See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

[1] Substance with a Community workplace exposure limit (see section 8.1).

### **SECTION 4: FIRST AID MEASURES.**

IRRITANT PREPARATION. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

### 4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

### Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

### Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

## Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

### Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate. Can cause allergic reactions.

It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

### 4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Cover the affected area with a dry sterile bandage. Protect the affected area from pressure or friction.

### SECTION 5: FIREFIGHTING MEASURES.

Flammable product, the necessary prevention measures should be taken in order to avoid risks, In case of fire, the following measures are recommended:

## 5.1 Extinguishing media.

(in accordance with Regulation (EU) 2015/830)

# FPM 302 Platinum light

 Version: 6
 Page 5 of 19

 Revision date: 30/08/2018
 Print date: 30/08/2018



Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

#### Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

### 5.2 Special hazards arising from the mixture.

#### Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:

- Flammable vapors or gases.

### 5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment. Follow the instructions given in the emergency or fire evacuation plan or plans if available.

### Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

### **SECTION 6: ACCIDENTAL RELEASE MEASURES.**

### 6.1 Personal precautions, protective equipment and emergency procedures.

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

### 6.2 Environmental precautions.

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

### 6.3 Methods and material for containment and cleaning up.

Pick up the spill with non-combustible absorbent materials (soil, sand, vermiculite, diatomite, etc.). Pour the product and the absorbent in an appropriate container. The contaminated area should be immediately cleaned with an appropriate decontaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

## 6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8. For later elimination of waste, follow the recommendations under section 13.

## **SECTION 7: HANDLING AND STORAGE.**

### 7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use antistatic footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks.For personal protection, see section 8.


In the application area, smoking, eating, and drinking must be prohibited. Follow legislation on occupational health and safety.

(in accordance with Regulation (EU) 2015/830)

# Z2380018L Platinum

 Version: 6
 Page 6 of 19

 Revision date: 30/08/2018
 Print date: 30/08/2018



## 7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 35° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

Classification and threshold amount of storage in accordance with Annex I to Directive 2012/18/EU (SEVESO III):

		Qualifying quant the applic	* ` *
Code	Description	Lower-tier requirements	Upper-tier requirements
H2	ACUTE TOXIC	50	200

### 7.3 Specific end use(s).

Not available.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

### 8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m³
		Koninkrijk	Eight hours	10	40,8
		België/Royaum e de Belgique/König reich Belgien [1]	Short term	20	81,6
		European	Eight hours	10 (skin)	40,8 (skin)
		Union [2]	Short term	20 (skin)	81,6 (skin)
cyclohexanone	108-94-1	United	Eight hours	10	41
		Kingdom [3]	Short term	20	82
		United States	Eight hours	25	
		[4] (Cal/OSHA)	Short term		
		United States	Eight hours	25	200
		[5] (NIOSH)	Short term		
		United States	Eight hours	50	
		[6] (OSHA)	Short term		
		Koninkrijk	Eight hours	2	12
Camphor	76-22-2	België/Royaum e de Belgique/König reich Belgien [1]	Short term	3	19
Rosin	8050-09-7	United	Eight hours		0,05
KUSIII	8030-09-7	Kingdom [3]	Short term		0,15
1,3,5-trimethylbenzene,mesitylene	108-67-8	Koninkrijk	Eight hours	20	100

(in accordance with Regulation (EU) 2015/830)

# FPM 302 Platinum light

 Version: 6
 Page 7 of 19

 Revision date: 30/08/2018
 Print date: 30/08/2018



		elgi /Royaum e de elgique/K nig reich elgien 1	Short term		
		European Union 2	Eight hours Short term	20	100
		Koninkri k	Eight hours	20	
delta-3-Carene	13466-78-9	elgi /Royaum e de elgique/K nig reich elgien 1	Short term		
		Koninkri k	Eight hours	20	
3,7,7-trimethylbicyclo 4.1.0 hept-3-ene	13466-78-9	elgi /Royaum e de elgique/K nig reich elgien 1	Short term		
		Koninkri k	Eight hours		5
Asphalt	8052-42-4	elgi /Royaum e de elgique/K nig reich elgien 1	Short term		
		United	Eight hours	_	5
1 According " player Limitor d		Kingdom 3	Short term		10

- According " aleurs Limites d Exposition Professionnelle" ( LEP) or " renswaarden voor eroepsmatige lootstelling" ( W ) list adopted by elgian Ministry of Employment and Labour.
- 2 According both inding ccupational Esposure Limits ( EL s) and Indicative ccupational Exposure Limits (I EL s) adopted by Scientific Committee for ccupational Exposure Limits to Chemical Agents (SC EL).
- 3 According Limit alue (I  $\,$  EL  $\,$ ) list in 2nd Indicative  $\,$  ccupational Exposure adobted by Health and Safety Executive.
- 4 California Division of ccupational Safety and Health (Cal/ SHA) Permissible Exposure Limits (PELs).
- 5 National Institute for ccupational Safety and Health. NI SH Recommendations for occupational safety and health, Compendium of Policy Documents and Statements, anuary, 1992, DHHS (NI SH) Publication No. 92-100.
- 6 ccupational Safety and Health Administration, United States Department of Labor. Permissible Exposure limits (PELs), California Division of ccupational Safety and Health (Cal/ SHA) Permissible Exposure Limits (PELs). The product does N T contain substances with iological Limit alues. Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Туре	Value
	DNEL (Workers)	Inhalation, Long-term, Local effects	40 (mg/m )
	DNEL ( eneral population)	Inhalation, Long-term, Local effects	20 (mg/m )
	DNEL (Workers)	Inhalation, Long-term, Systemic effects	40 (mg/m )
cyclohexanone CAS	DNEL ( eneral population)	Inhalation, Long-term, Systemic effects	10 (mg/m )
No: 108-94-1 EC No: 203-631-1	DNEL (Workers)	Inhalation, Acute, Systemic effects	80 (mg/m )
	DNEL ( eneral population)	Inhalation, Acute, Systemic effects	20 (mg/m )
	DNEL (Workers)	Inhalation, Acute, Local effects	80 (mg/m )
	DNEL ( eneral population)	Inhalation, Acute, Local effects	40 (mg/m )

(in accordance with Regulation (EU) 2015/830)

# Z2380018L Platinum

 Version: 6
 Page 8 of 19

 Revision date: 30/08/2018
 Print date: 30/08/2018



	DNEL (Workers)	Dermal, Long-term, Systemic effects	4 (mg/kg bw/day)
	DNEL (eneral population)	Dermal, Long-term, Systemic effects	1 (mg/kg bw/day)
	DNEL (Workers)	Dermal, Acute, Systemic effects	4 (mg/kg bw/day)
	DNEL ( eneral population)	Dermal, Acute, Systemic effects	1 (mg/kg bw/day)
	DNEL ( eneral population)	ral, Long-term and acute, Systemic effects	1,5 (mg/kg bw/day)
Rosin CAS No: 8050-09-7 EC No: 232-475-7	DNEL (Workers)	Inhalation, Long-term, Systemic effects	176 (mg/m )
1,3,5-trimethylbenzene,mesitylene	DNEL (Workers)	Inhalation, Long-term, Local effects	100 (mg/m )
CAS No: 108-67-8 EC No: 203-604-4	DNEL (Workers)	Inhalation, Long-term, Systemic effects	100 (mg/m )
delta-3-Carene CAS No: 13466-78-9 EC No: 236-719-3	DNEL (Workers)	Inhalation, Long-term, Systemic effects	5,98 (mg/m )
3,7,7-trimethylbicyclo 4.1.0 hept-3-ene CAS No: 13466-78-9 EC No: 236-719-3	DNEL (Workers)	Inhalation, Long-term, Systemic effects	5,98 (mg/m )
Asphalt CAS No: 8052-42-4 EC No: 232-490-9	DNEL (Workers)	Inhalation, Long-term, Local effects	2,9 (mg/m )

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
cyclohexanone CAS No: 108-94-1 EC No: 203-631-1	Fresh water	0,033 (mg/l)
	Agua de mar	0,003 (mg/l)
	STP	10 (mg/l)
	Sedimento agua dulce	0,168 (mg/kg)
	Sedimento agua de mar	0,017 (mg/kg)
	Soil	0,014 (mg/kg)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

### 8.2 Exposure controls.

## **Measures of a technical nature:**

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %
Uses:	Ceramic use.
Breathing protecti	on:
PPE:	Filter mask for protection against gases and particles (A-P).
	Category I, II or III should be chosen depending on the use limit value. The mask
Characteristics: must	be comfortable and tight to the face.

(in accordance with Regulation (EU) 2015/830)

# FPM 302 Platinum light



 Version: 6
 Page 9 of 19

 Revision date: 30/08/2018
 Print date: 30/08/2018

CEN standards: EN 149 Avoid exposure to high temperatures when not used. Before use, check the integrity of inspiration and Maintenance: expiration valves. Use when exceeding TLV for one or more substances conteined in the mixture. Be sure that the Observations: equipment is efficient. Hand protection: Protective gloves against chemicals. Characteristics: «CE» marking, category III. CEN standards: EN 374-1, En 374-2, EN 374-3, EN 420 Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much Do not make any changes to the gloves that may alter their resistance, or apply paints, solve Maintenance: ıS ts possible. adhesives. Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too ight. Observations: Always use with clean, dry hands. Material thickness 0,3 5 Breakthrough time Material: PVC (polyvinyl chloride > 480 (mm): (min.): Eye protection: PPE: Protective goggles against splashes and particles. Characteristics: CEN standards: Maintenance: Under normal and reasonably foreseeable conditions, eye protection is not required. However, protective Observations: goggles are recommended when handling the product to avoid accidental sketching of liquids. Skin protection: If the product is handled correctly, no individual protection equipment is necessary.

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

# 9.1 Information on basic physical and chemical properties.

Appearance:Liquid with characteristic odour and colour

Colour: not available
Odour:characteristic Odour
threshold:not available
pH:N.A./N.A.

Maltina naint

Melting point:not available °C Boiling Point: 180 °C Flash point: 50 °C

Evaporation rate: not available

Inflammability (solid, gas): not available

Lower Explosive Limit: It does not contain chemical groups associated with explosive properties Upper

Explosive Limit: It does not contain chemical groups associated with explosive properties

Vapour pressure: 1,886

(in accordance with Regulation (EU) 2015/830)

# Z2380018L Platinum

Version: 6 Page 10 of 19
Revision date: 30/08/2018 Print date: 30/08/2018

Vapour density:not available Relative density:0,939 Solubility:N.A./N.A. Liposolubility: N.A./N.A. Hydrosolubility: N.A./N.A.

Partition coefficient (n-octanol/water): not available Auto-ignition temperature: not available°C Decomposition temperature: not available°C

Viscosity: N.A./N.A.

Explosive properties: It does not contain chemical groups associated with explosive properties Oxidizing

properties: It does not contain chemical groups associated with oxdizing properties

N.A./N.A. = Not Available/Not Applicable due to the nature of the product

### 9.2 Other information.

Pour point: not available Blink: not available

Kinematic viscosity: N.A./N.A.

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

### SECTION 10: STABILITY AND REACTIVITY.

### 10.1 Reactivity.

If the storage conditions are satisfied, does not produce dangerous reactions.

#### 10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

## 10.3 Possibility of hazardous reactions.

Flammable liquid and vapour.

### 10.4 Conditions to avoid.

Avoid the following conditions:

- High temperature.
- Static discharge.
- Contact with incompatible materials.
- Avoid temperatures near or above the flash point. Do not heat closed containers. Avoid direct sunlight and heat, as these may cause a risk of fire.

### 10.5 Incompatible materials. Avoid

the following materials:

- Explosives materials.
- Toxic materials.
- Oxidizing materials.

### 10.6 Hazardous decomposition products.

In case of fire, dangerous decomposition products can be generated, such as carbon monoxide and dioxide and nitrogen fumes and oxides.

### **SECTION 11: TOXICOLOGICAL INFORMATION.**

IRRITANT PREPARATION. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

### 11.1 Information on toxicological effects.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin. Splatters in the eyes can cause irritation and reversible damage.

Toxicological information about the substances present in the composition.

(in accordance ith Regulation (E ) 201 /830)

# **FPM 302 Platinum light**



Name		Acute toxicity			
Name	Туре	Test	Kind	Value	
c clohexanone	Oral	LD 0 1 America Pg. 70 19		800 mg/ g 1 giene Association ournal. Vol. 30	
CAS No: 108-9 -1 EC No: 203-631-1	Inhalation	197 . Vol.	Rat Material Data H 1 Pg. 18 197	11.8 mg/l/ h 1 landboo Vol.1: Organic Solvents	
	Oral	LD 0	Торо	1 00 mg/ g	
Camphor	Dermal	LD 0	Ratto	2000 mg/ g	
CAS No: 76-22-2 EC No: 200-9 -0	Inhalation	LC 0	Ratto	00 mg/ g	
	Oral	DL 0	Rat	2800 mg/ g	
Rosin	Dermal				
CAS No: 80 0-09-7	Inhalation				
	Oral				
13 -trimeth Ibenzene nesit lene	Dermal	LC 0	Rat	2 mg/l/ h 1	
CAS No: 108-67-8 EC No: 203-60 -	Inhalation	1 Vol. () 1979	jiena i Sanitari p transla	i a. For En see HYSAAV.	
	Oral			800 mg/ g 1 800 mg/ g 2 oxicolog . Vol. 11 Pg. 10 3 1973 oxicolog . Vol. 11 Pg. 10 3 1973	
3 7 7-trimeth Ibic clo .1.0 hept-3-ene	Dermal				
CAS No: 13 66-78-9 EC No: 236-719-3	Inhalation				

a) acute toxicit

Not conclusive data for classification.

Acute Toxicit Estimate (ATE):

Mixtures:

ATE (Oral) 6.393 mg/ g

b) s in corrosion/irritation Product classified: S in irritant Categor 2: Causes s in irritation.

c) serious e e damage/irritation ased on available data the classification criteria are not met.

d) respirator or s in sensitisation Product classified:

**GLAZURA** 

(in accordance ith Regulation (E ) 201 /830)

# Z2380018L Platinum

Version: 6

Revision date: 30/08/2018



Page 12 of 19 Print date: 30/08/2018

S in sensitiser Categor 1: Ma cause an allergic s in reaction.

e) germ cell mutagenicit ased on available data the classification criteria are not met.

f) carcinogenicit ased on available data the classification criteria are not met.

g) reproductive toxicit Not conclusive data for classification.

h) STOT-single exposure ased on available data the classification criteria are not met.

i) STOT-repeated exposure

(in accordance ith Regulation (E ) 201 /830)

# **Z2380018L Platinum**

 Version: 6
 Page 13 of 19

 Revision date: 30/08/2018
 Print date: 30/08/2018

Not conclusive data for classification.

) aspiration hazard ased on available data the classification criteria are not met.

## **SECTION 12: ECOLOGICAL INFORMATION.**

### 12.1 Toxicity.

	Ecotoxicity			
Name	Туре	Test	Kind	Value
	Fish			72-732 mg/l (96 h) 1 A Committee on Methods for
c clohexanone	A uatic invertebrates	FC 0  1 OECD (Test)	Daphnia magna	100 mg/l ( 8h) 1 nia sp. Acute Immobilisation
CAS No: 108-9 -1 EC No: 203-631-1	A uatic plants	ECr 0	Desmodesmus subspicatus	100 mg/l (72h) 1  Gro th Inhibition Test)
	Fish	1 rennin Continuous Outboard N	Fish man G. R. Hartung Flo ioassa Meth	12 mg/l (96 h) 1 and eber r. 1976. A od to Evaluate the Effects of elected Aromatic Toxicants
	A uatic invertebrates	LC 0  1 Cald e Effects of a Oil and Its	Crustacean  II R.S. E.M. Caldaro a Sea ater-Soluble Fi B Ma or Aromatic Con	13 mg/l ( 8 h) 1 ne and M.H. Mallon 1977. raction of Coo Inlet Crude nponents on Larval Stages of agister Dana. In: D.A. offe
13 -trimeth Ibenzene mesit lene CAS No: 108-67-8 EC No: 203-60 -	A uatic plants	-		

### 12.2 Persistence and degradability.

There is no information available on the degradabilit of the substances present.

No information is available regarding the degradabilit of the substances present. No information is available about persistence and degradabilit of the product.

### 12.3 Bioaccumulative potential.


Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
	Log Pow	BCF	NOECs	Level

(in accordance ith Regulation (E ) 201 /830)

# Z2380018L Platinum

Version: 6 Page 14 of 19
Revision date: 30/08/2018 Print date: 30/08/2018



38

12.4 Mobility in soil.

3 7 7-trimeth lbic clo .1.0 hept-3-ene

N. CAS: 13 66-78-9

No information is available about the mobilit in soil. The product must not be allo ed to go into se ers or ater a s. Prevent penetration into the ground.

EC No: 236-719-3

12.5 Results of PBT and vPvB assessment.

No information is available about the results of P T and vPv assessment of the product.

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

# **SECTION 13 DISPOSAL CONSIDERATIONS.**

### 13.1 Waste treatment methods.

Do not dump into se ers or ater a s. aste and empt containers must be handled and eliminated according to current local/national legislation.

Follo the provisions of Directive 2008/98/EC regarding aste management.

### **SECTION 14: TRANSPORT INFORMATION.**

Transport follo ing ADR rules for road transport RID rules for rail a ADN for inner ater a s IMDG for sea and ICAO/IATA for air transport.

Land: Transport b road: ADR Transport b rail: RID.

Transport documentation: Consignment note and ritten instructions Sea: Transport b ship: IMDG. Transport documentation: ill of

lading <u>Air</u>: Transport b plane: ICAO/IATA.

Transport document: Air a bill.

14.1 UN number. N No: N1263

14.2 UN proper shipping name.

Description:

ADR: N 1263 PAINT RELATED MATERIAL 3 PG III (D/E)

IMDG: N 1263 PAINT RELATED MATERIAL (E CALYPT S GLO L S OIL) 3 PG III MARINE POLL TANT

ICAO/IATA: N 1263 PAINT RELATED MATERIAL 3 PG III

14.3 Transport hazard class(es).

Class(es): 3

High

(in accordance with Regulation (EU) 2015/830)

# Z2380018L Platinum

Version: 6

**14.4 Packing group.** Packing group: III



Page 15 of 19

Revision date: 30/08/2018 Print date: 30/08/2018

### 14.5 Environmental hazards.

Marine pollutant: Yes



Dangerous for the environment

### 14.6 Special precautions for user.

Labels: 3



Hazard number: 30 ADR LQ: 5 L IMDG LQ: 5 L ICAO LQ: 10 L

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR. Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-E,S-E Proceed in accordance with point 6.

## 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code. The

product is not transported in bulk.

### **SECTION 15: REGULATORY INFORMATION.**

## 15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC) VOC content (p/p): 9,335 % VOC content: 87,638 g/l

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): H2

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

### 15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

### **SECTION 16: OTHER INFORMATION.**

(in accordance with Regulation (EU) 2015/830)

# Z2380018L Platinum

 Version: 6
 Page 16 of 19

 Revision date: 30/08/2018
 Print date: 30/08/2018

Complete text of the H phrases that appear in section 3:

H224	Extremely flammable liquid and vapour.			
H226	Flammable liquid and vapour.			
H228	Flammable solid.			
H302	Harmful if swallowed.			
H304	May be fatal if swallowed and enters			
	airways.			
H315	Causes skin irritation.			
H317	May cause an allergic skin reaction.			
H319	Causes serious eye irritation.			
H332	Harmful if inhaled.			
H335	May cause respiratory irritation.			
H341	Suspected of causing genetic defects.			
H351	Suspected of causing cancer.			
H371	May cause damage to organs.			
H400	Very toxic to aquatic life.			
H410	Very toxic to aquatic life with long lasting			
	effects.			
H411	Toxic to aquatic life with long lasting effects.			

#### Classification codes:

Acute Tox. 4 : Acute toxicity (Inhalation), Category 4

Acute Tox. 4: Acute toxicity (Oral), Category 4

Aquatic Acute 1 : Acute toxicity to the aquatic environment, Category 1 Aquatic Chronic 1 : Chronic effect to the aquatic environment, Category 1 Aquatic Chronic 2 : Chronic effect to the aquatic environment, Category 2

 $\mbox{Asp. Tox. 1: Aspiration toxicity, Category 1} \\$ 

Carc. 2 : Carcinogen, Category 2
Eye Irrit. 2 : Eye irritation, Category 2
Flam. Liq. 1 : Flammable liquid, Category 1
Flam. Liq. 3 : Flammable liquid, Category 3
Flam. Sol. 2 : Flammable solid, Category 2
Muta. 2 : Mutagen, Category 2

Muta. 2 : Mutagen, Category 2 Skin Irrit. 2 : Skin irritant, Category 2 Skin Sens. 1 : Skin sensitiser, Category 1 Skin Sens. 1A : Skin sensitiser, Category 1A Skin Sens. 1B : Skin sensitiser, Category 1B

STOT SE 2 : Specific target organ toxicity following a single exposure, Category 2 STOT

SE 3: Specific target organ toxicity following a single exposure, Category 3

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Information on the TSCA Inventory (Toxic Substances Control Act) USA:

CAS No	Name	State
84625-32-1	Eucalyptus globulus oil	
8000-25-7	Rosemary oil N. Afr.	Registered
108-94-1	cyclohexanone	Registered
76-22-2	Camphor	Registered
8050-09-7	Rosin	Registered
94266-48-5	Pine exctract	
108-67-8	1,3,5-trimethylbenzene,mesitylene	Registered

(in accordance with Regulation (EU) 2015/830)

# Z2380018L Platinum



Version: 6 Page 17 of 19

68956-56-9	Hydrocarbons, terpene processing by-products	Registered
99-86-5	alpha-Terpinene	Registered
138-86-3	Dipentene	Registered
13466-78-9	delta-3-Carene	Registered
70879-65-1	2-Naphthalenol, 1-[[4-(phenylazo)phenyl]azo]-, ar',ar"-Me derivs.	Registered
13466-78-9	3,7,7-trimethylbicyclo[4.1.0]hept-3-ene	Registered
8052-42-4	Asphalt	Registered

Abbreviations and acronyms used:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

BCF: Bioconcentration factor.

CEN: European Committee for Standardization.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be

(in accordance with Regulation (EU) 2015/830)

# Z2380018L Platinum

Version: 6
Revision date: 30/08/2018

Page 18 of 19

**GLAZURA** 

Print date: 30/08/2018

considered a tolerable minimum.

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not

anticipated.

EC50: Half maximal effective concentration.

PPE: Personal protection equipment.

IATA: International Air Transport Association.

ICAO: International Civil Aviation Organization.

IMDG: International Maritime Code for Dangerous Goods.

LC50: Lethal concentration, 50%.

LD50: Lethal dose, 50%.

Log Pow: Logarithm of the partition octanol-water. NOEC: No observed effect concentration.

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are

not expected in the environmental compartment.

RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

Key literature references and sources for data:

http://eur-lex.europa.eu/homepage.html http://echa.europa.eu/ Regulation

(EU) 2015/830.

Regulation (EC) No 1907/2006. Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.

(in accordance with Regulation (EU) 2015/830)

# Z2380018L Platinum

Version: 6



Page 19 of 19 End of safety data sheet.-